

NLG Super Bungee Chainsaw Lanyard, O-Ring

Product Code:
101623

Max Load:
10 KG / 22 LBS




OVERVIEW

The Super Bungee Chainsaw Lanyard, O ring is the ultimate solution to securing your chainsaw whilst working at height. The Super Bungee provides a compact footprint whilst the easy-stretch nature allows 2 metres of reach. The lanyard is complete with a metal O ring for easy docking.

VIEW ONLINE

<https://neverletgo.com/products/super-bungee-chainsaw-lanyard-ring/>



NLG ID™
Serialised and safe

Simply scan the NLG ID tag with your phone to instantly access certificates, instruction videos and log inspections. (See Specification if included).



Third-party tested and certified

Independent laboratory load testing certificates and Declarations of Conformity are available on request. Please contact team@neverletgo.com.

DESCRIPTION

The result of a long development, working closely with the Arb Industry, The Super Bungee Chainsaw lanyard is the benchmark for chainsaw lanyards. The lanyard uses unique SoftTouch™ webbing which remains supple in the harshest working environments, whilst the Super Bungee both dampens forces in the event of a drop and provides all-day comfort. With safety in mind, the visual wear indicator strips provide a quick and easy check for inspection prior to use and allow damage affecting the integrity of the lanyard to be easily identified. Complete with a durable metal O ring for easy docking and a lay-flat loop, providing a low-profile attachment point for either the tool or harness for safety and comfort.

FEATURES

Ultra-durable wear-resistant Soft Touch™ Nylon Webbing
 Easy visual inspection with contrast stitching and edges
 Compact Super Bungee reduces snagging hazards whilst providing easy reach and extension
 Reduced shock loading due to clever bungee design
 Lay flat webbing loops ensure low profile attachment points on the tool and harness for safety and comfort in use.
 Heavy-duty O-ring for easy holstering

TECHNICAL SPECIFICATION

Max Load: 10 KG / 22 LBS
 Safety Standards: ANSI/ISEA 121-2018, CE / UKCA, NS 9611:2022+AC
 Load Tested and Third-party Certified: Dynamic (2:1 Safety Factor)
 NLG ID™ Technology / Scannable Compatible
 Unique Serial Number
 Dimensions: Extends from 80cm to 200cm

RETAIL

EAN (GTIN-13)
 5060572181014

UNIT WEIGHT (G)
 210

SHIPPING

HS CODE
 5609.00.0000

COUNTRY OF ORIGIN
 Taiwan



Super Bungee Chainsaw Lanyard, O-Ring
Product Code: 101623

View online

<https://neverletgo.com/products/super-bungee-chainsaw-lanyard-ring/>

Learn more about:

[Dropped object prevention](#)

[Tool tethering](#)

[Tool lanyards](#)

Useful resources:

[Tool Box](#)

[Tool Tether Guide](#)

[Library](#)

CONTACT

+44 (0)330 016 0030

neverletgo.com

INSPECTION

In addition to routine checks before each use, all equipment should undergo regular detailed inspections, conducted and recorded by a competent person using the NLG Inspection Checklist. If any part is worn or shows signs of degradation, immediately retire from service. In the event of a drop, quarantine the equipment for a thorough inspection.

[Click to download Inspection Checklist](#)

LEGAL

NLG makes every effort to ensure the information in this Datasheet is accurate and current. However, NLG reserves the right to change the product specification when necessary. NLG cannot be held responsible for any inaccuracies or omissions.

Copyright © 2023. NLG® and Never Let Go® are registered trademarks.
