



INSTRUCTIONS

LINESMAN TOOL POUCH WITH RETRACTABLES

CODE
↳101750

MAX LOAD
↳5KG / 11LBS

NLG ID
Scan the orange tags on compatible NLG products to access detailed product info, certification and installation videos.

NOTE
Max weight in the pouch 5KG.
Max weight of a tool on each retractable lanyard is 0.5kg

01

Using the two D rings on the rear of the pouch, attach two compatible connectors and connect the pouch to a harness or work belt. Also compatible with the NLG Shoulder Strap (101703)

02

Ensure that all tools in the pouch are secured via a lanyard to a D ring in the pouch or using the integrated retractable lanyards.

03

Intergrated D rings: No single tool should be above 5KG

Intergrated retractable lanyards: Each lanyard has 0.5KG load rating.

04

Ensure that the compartments are securely closed before climbing or descending.



INSTRUCTIONS

INSTALLING THE RETRACTABLE LANYARDS

CODE

↳101750

NLG ID

Scan the orange tags on compatible NLG products to access detailed product info, certification and installation videos.

NOTE

Max weight in the pouch 5KG.
Max weight of a tool on each retractable lanyard is 0.5kg

01

Remove the split ring from the end of the lanyard.

02

Peel open the velcro at the bottom of the required elasticated pocket and slide the retractable lanyard into the pocket. Reseat the velcro patch. Pull the cable through the top of the elasticated pocket.

03

Pass the end of the lanyard through the grommet hole into the pouch and reattach the ring to the end of the lanyard.

04

The tool can be attached directly to the ring if it has a hole or by using an appropriate connector.

Note: The max load per retractable is 0.5KG