



## INSTRUCTIONS

# LINESMAN TOOL POUCH

### CODE

↳101751

### MAX LOAD

↳5KG / 11LBS

### NLG ID

Scan the orange tags on compatible NLG products to access detailed product info, certification and installation videos.

### NOTE

Max weight in the pouch 5KG.  
No single tool above 5KG to a D ring.

**01**

Using the two D rings on the rear of the pouch, attach two compatible connectors and connect the pouch to a harness or work belt. Also compatible with the NLG Shoulder Strap (101703)

**02**

Ensure that all tools in the pouch are secured via a lanyard to a D ring in the pouch.

**03**

Ensure that the compartments are securely closed before climbing or descending.

**04**

Note: The NLG Mini Retractable Tool Lanyard (101480) can be retrofitted to the Linesman Pouch. Please see next page for installation instructions.



## INSTRUCTIONS

# INSTALLING THE RETRACTABLE LANYARDS

### CODE

↳101751

### NLG ID

Scan the orange tags on compatible NLG products to access detailed product info, certification and installation videos.

### NOTE

Max weight in the pouch 5KG.  
Max weight of a tool on each retractable lanyard is 0.5kg

**01**

Remove the split ring from the end of the lanyard.

**02**

Peel open the velcro at the bottom of the required elasticated pocket and slide the retractable lanyard into the pocket. Reseat the velcro patch. Pull the cable through the top of the elasticated pocket.

**03**

Pass the end of the lanyard through the grommet hole into the pouch and reattach the ring to the end of the lanyard.

**04**

The tool can be attached directly to the ring if it has a hole or by using an appropriate connector.

Note: The max load per retractable is 0.5KG